

PRO START 2824 12-24V code 829517

Battery-powered starter suitable for 12-24V starting of cars, vans, boats, agricultural vehicles, power sources etc. When connected to the cigar-lighter outlet it maintains the voltage on all circuits during battery changes and is also a 12V power source for use in emergencies. Fit with a safety switch for starting, it does not damage the electronics of the vehicle and allows for a large number of starting operations before being recharged. PRO START 2824 can be recharged using the special power supply, connected to the mains network, or using the cigar-lighter outlet of the vehicle (for the safeguard of the battery, charge for 12 hours before use, charge again after each use and every 3 months in any case). Characteristics: safety switch * overload protection * polarity reversal protection acoustic/luminous alarm * high efficiency led lamp * battery charge status led * battery charging status led * 2 x 12V jack sockets * cable-holder pocket. Complete with: 230V AC 12V DC power adaptor, positive-negative cables with clamps, high efficiency lamp, double jack cable.



AUTOMOTIVE

PROFESSIONAL



Technical Data

Standards:	LVD: EN 61558-1	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3				
CODE	V _{PH}	START	A _h	A _{OUT}	A _{START MAX}	W _H	kg
829517	V 230 1 ph	V 12 24	Ah 44 22	A 800	A 2500	mm(L,W,H) 205 335 360	kg 16,1
BAR CODE							
800489783756 7	pz/pallet 26	pz/pallet - B 39					