

## STARTRONIC 530 230V code 829034

Digital, microprocessor controlled battery charger and starter for charging all types of batteries (WET, GEL, AGM), with 6/12/24V voltage and starting of cars, vans and trucks. Startronic protects the on-board electronic such as ABS, airbag, electronic injection, etc. Running modes: TEST, CHARGE, TRONIC, START and STAND-BY. The STAND-BY function is activated through connection to the cigarette lighter outlet of the car, it allows to disconnect and charge the car battery without erasing the preset values of the on-board computer. The TRONIC function allows for the electronic control of charging current, automatic interruption and restart. The new implemented technology SAFE START does not damage the on-board electronics during the starting phase (START) because it eliminates the overvoltages typical of the traditional starters. Characteristics: choice of charge current 1÷40A \* display to check battery voltage, charging current and time \* display to check battery status \* protection against reverse polarity, battery failure, thermostatic interruption, faulty battery charger.



### AUTOMOTIVE



## Technical Data

Standards:	LVD: EN 60335-2-29	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3					
<b>CODE</b>	<b>V<sub>PH</sub></b>	<b>P<sub>C/S</sub></b>	<b>+ - START</b>	<b>+ - START</b>	<b>A<sub>MIN</sub> A<sub>MAX</sub></b>	<b>A<sub>EFF</sub></b>	<b>A<sub>EN</sub></b>	
829034	V50/60Hz 230 1 ph	kW 1,5 9,5	V 6 12 24	V 12 24	A 1 40	A 75	A 40	
<b>A<sub>1V/C</sub></b>	<b>A<sub>START MAX</sub></b>	<b>C<sub>MIN/MAX</sub></b>	<b>W<sub>H</sub> L</b>	<b>kg</b>	<b>BAR CODE</b>	<b>pz/pallet</b>	<b>pz/pallet - B</b>	
A 300	A 400	Ah15h 10 600	mm(L,W,H) 390 260 230	kg 19,5	800489771274 1	18	12	