

## T-CHARGE 12 12V code 807560

Single-phase, portable, intelligent battery charger with electronic control of the charging current and automatic interruption and restart. Fit for charging sealed (GEL) and free-electrolyte lead batteries (WET) with 12V voltage of motorcycles, cars and vans. Main characteristics: selection of 3 charge current levels \* warning led indicating charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal. \* water spray resistant \* reduced dimensions and weight \* supplied with three different charging cables.



### AUTOMOTIVE

### CONSUMER



### AUTOMATIC CONTROL OF THE CHARGE LEVEL



### CHARGING STATUS WARNING LED



### WIDE RANGE OF USE



### SHORT-CIRCUIT, POLARITY REVERSAL



### 3 DIFFERENT TYPES OF CHARGING CABLES



## Technical Data

Standards:	LVD: EN 60335-2-29	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3				
CODE	V <sub>PH</sub>	P	START	A <sub>EFF</sub>	A <sub>EN</sub>	C <sub>MIN/MAX</sub>	
807560	V50/60Hz 230 1 ph	W 55	V 12	A 4	A 4	Ah15h 2 70	3
W <sub>H</sub>	kg	BAR CODE					
mm(L,W,H) 170 65 35	kg 0,6	800489771248 2	pz/pallet 420				