
☐HGL2.3-12






Specifications

Nominal Voltage		12V
Rated Capacity (20 hour rate)		2.3AH
Dimension	Total Height (with terminals)	67mm(2.64inches)
	Height	61mm(2.40 inches)
	Length	177mm(6.97inches)
	Width	35mm(1.38inches)
Weight		Approx.0.92kg (2.03Ibs)


Discharge characteristics 77℉(25℃)



Characteristics

Capacity 77℉(25℃)	20 hour rate (115m A to 10.5Volts)	2.3AH
	10 hour rate (214mA to10.5Volts)	2.14AH
	5 hour rate (392mA to 10.2Volts)	1.96AH
	1 hour rate (1.38A to 9.6Volts)	1.38AH
Internal Resistance	Full charged 77℉(25℃)	60mΩ
Standard Terminal	F1	
Capacity affected by Temperature (20 hour rate)	104℉(40℃)	102%
	77℉(25℃)	100%
	32℉(0℃)	85%
	5℉(-15℃)	65%
Self-Discharge 77℉(25℃)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Max. Discharge Current 77℉(25℃)	30A (5s)	
Maximum Charge Current(A)	460mA	
Charging (Constant Voltage)	Cycle	14.5V～14.9V/77℉(25℃)
	Float	13.6V～13.8V/77℉(25℃)
Temperature compensation coefficient of charging voltage (mV/℃/cell)	Cycle	-4mV/°C/cell
	Float	-3mV/°C/cell

Duration of discharge vs. Discharge current



Constant Current Discharge Rating Amperes @ 77℉(25℃)

Cut off voltage V/cell	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	20H
1.75V	3.78	2.36	1.67	1.32	0.76	0.56	0.39	0.26	0.21	0.18	0.12

Note The above data are average values, and can be obtained with 3 charge/discharge cycles. These are not minimum values.

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specification are subject to modification without notice. Contact Fullriver for the latest information.