TECHNICAL DATA SHEET

Type no.	EFB 565 00

Article no.	012565000101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery

Electrical data	
Rated voltage	12V
Rated capacity	65 Ah (K20)
Cold start current	550 A (EN)

Dimensions and weights		
Box	D23	 Symbolpicture
Length max.	233mm	
Width max.	173mm	
Box height max.	203mm	
Total height max.	225mm	
Battery weight	Ca. 17,5 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		60
Pallet ID		Euro pallet
Items per layer		20

Features	
Base hold-down	B00
Layout	0
Terminal	1
Separator	PE bag separator with glass nonwoven
Degassing	Battery with central degassing
Flame arrester	Integrated

Maintenance [1])	
Water consumption	< 1g/Ah
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage [2])	max. 14,8 V

[1]) All the listed values relate to room temperature +25° C
[2]) Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original

Banner GmbH, A-4021 Linz, Banner Straße 1
Tel. +43/(0)732/38 88-0, e-mail: internet@bannerbatterien.com

THE POWER COMPANY