



## 6FS-400 FS Series

Rolls 6V 400Ah (C20) Deep Cycle Battery



RESERVE CAPACITY	CCA	
@25AMPS	MCA@0°C	CCA@-18°C
870 Mins.	1523	1218

SPECIFICATIONS		
Nominal Voltage		6 Volt
Rated Capacity (20 hour rate)		400Ah
Dimensions	Height	425mm
	Length	316mm
	Width	178mm
Weight		53 Kg

PLATES		
Cells		3
Plates/Cell		17
Positive Plate Dimension	Height	273mm
	Width	143mm
	Thickness	4.32mm
Negative Plate Dimension	Height	273mm
	Width	143mm
	Thickness	3.05mm
Separator Thickness		2mm
Insulation Glass Mat		1mm

CHARACTERISTICS		
Capacity 77°F (25°C)	20 Hour Rate	400 Ah
	10 Hour Rate	352 Ah
	5 Hour Rate	295 Ah
Current (Amps)	20 Hour Rate	20
	10 Hour Rate	35.2
	5 Hour Rate	59
Electrolyte Reserve Above Plates		57 mm

CONTAINER CONSTRUCTION	
Container	High Density Polypropylene
Cover	High Density Polypropylene
Terminals	Lug Terminal
Handles	Rope

SIZE & DETAILED ILLUSTRATION		

This information is generally descriptive only and is not intended to make or imply and representation, guarantee or warranty with respect to any cells and batteries. Call and battery design/specifications are subject to modifications without notice. For further information contact Rolls Battery Europe.



**A Division of Barden UK Ltd.**

**T. +44 (0)1489 570770 E. info@rolls-battery.com www.rolls-battery.com**